

# LS32 SMA A4



## Specifications

ETI Code	004660065
Description	LS32 SMA A4
Class name	Switch disconnecter PV
Function	PV Switch disconnectors, 0-1
No. Of poles	4
Mounting	DIN-rail mounted
Thermal current I <sub>th</sub> (A)	32
Max. rated operational voltage U <sub>r</sub> (V)	1500
Rated operational current I <sub>e</sub> DC-21 B at 1000V DC (A)	32

Online product page 

## Other documentation



Technical data catalogue

3D Model

CE declaration

Eplan file

## ETIM international classification

Classification	EC000216
Class name	Switch disconnector
Mounting method	DIN-rail mounted
Number of knife blade fuse holders	4
Version as main switch	1
Version as maintenance-/service switch	1
Version as safety switch	1
Version as emergency stop installation	
Version as reversing switch	
Max. rated operation voltage Ue AC	440V
Rated operating voltage	300...1000V
Rated permanent current Iu	32A
Rated permanent current at AC-21, 400 V	32A
Conditioned rated short-circuit current Iq	5kA
Number of poles	4
Motor drive optional	
Motor drive integrated	
Voltage release optional	
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	
Suitable for front mounting 4-hole	
Suitable for front mounting centre	
Suitable for distribution board installation	1
Suitable for intermediate mounting	
Colour control element	Black
Type of control element	Turn button
Interlockable	
Type of electrical connection of main circuit	Frame clamp
Degree of protection (IP), front side	IP20